



SBC-160M24-20x-S165

鍍層厚度：

Blank : 1u"
2 : 15u"
3 : 30u"

PCB EDGE

RECOMMENDED P.C.B. LAYOUT

PIN ASSIGNMENT												BLADE	SHELL
A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12		
GND	TX1	TX1	VBUS	CC1	D+	D-	SBU1	VBUS	RX2	RX2	GND	GND	GND
GND	RX1+	RX1-	VBUS	SBU2	D-	D+	CC2	VBUS	TX2-	TX2+	GND		
B12	B1	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1		

SPECIFICATIONS

Electrical:

- Rating: 20V, 5.0 A
- Dielectric Withstand Voltage: 100V AC
- Contact Resistance: 30 mΩ Max
- Insulation Resistance: 100 MΩ Min

Mechanical:

- Connector Mate and Unmate Force
 - Mate force: 5~20 N
 - Unmate force: 8~20 N

Material:

- Housing: PA46
- Contact: C7025
- Shell: SUS

Finish:

- Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall
- Shell: Nickel under Plated surface layer

 广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	07/05/23
CHECKED BY:	DATE
Jacky Chen	07/05/23
APPROVED BY:	DATE
Tony Kao	07/05/23

MAT'L	
FINISH	
SCALE	1 : 1
SHEET NO.	1 of 1

TITLE	CONNECTOR
MODLE	USB TYPE C 2.0 沉板上H1.48mm CH0.10mm
DWG NO.	SBC-160M24-20x-S165
PART NO.	SBC-160M24-20x-S165

SIZE
A4
VER
R